

CENTER 317

HUMIDITY TEMPERATURE METER

(DEW POINT & WET BULB)



CE

Feature:

- Dew Point and Wet Bulb temperature Measurement.
- Fast response.
- Auto shut off for Battery Saving.
- MAX/MIN Function.
- Dual displays:
Primary display for Humidity;
Secondary displays for temperature.

CENTER®

CENTER 317 HUMIDITY TEMPERATURE METER

SPECIFICATIONS

Measurement Range:

Temperature: $-20^{\circ}\text{C}\sim 60^{\circ}\text{C}$; $-4^{\circ}\text{F}\sim 140^{\circ}\text{F}$

Humidity: 0%RH~99%RH

Resolution: $0.1^{\circ}\text{C}/0.1^{\circ}\text{F}/0.1\%RH$

Accuracy:

Temperature: $\pm 0.8^{\circ}\text{C}$, 1.6°F

Humidity: $\pm 2.5\%RH$

Sampling Rate: 2.5 times/sec

Humidity Sensor:

Electronic capacitance polymer film sensor.

Battery Type: 1.5V AA size battery x 4

Operating Condition: 0°C to 40°C ($<80\%RH$)

Dimensions: $210\times 65\times 43\text{mm}$

Accessories: Batteries, Instruction Manual




LED Back Light

1:1 Size



33%RH / 75%RH
Humidity Standard (OPTIONAL)

Dual Display



Primary display
for Humidity;
Secondary displays
for temperature.

Pull Up
Sensor
Protector.



CENTER[®]
CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http://www.centertek.com

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: **Impex Produkter AS**

Verkseier Furulunds vei 15
0668 OSLO
Tel. 22 32 77 20
Fax 22 32 77 25
info@impex.no
www.impex.no