

CENTER 326 Sound Level Calibrator



FEATURE :

- **Conforms to IEC 60942 (2003) class 2, ANSI S1.40-1984**
- **94dB and 114dB sound calibrator at 1kHz**
- **Accurate and simple to use**
- **Fits 1 inch and 1/2 inch microphones**



SPECIFICATION:

| | |
|----------------------------------|--|
| Output sound pressure levels | 114dB and 94dB re 20uPa under reference conditions |
| Output frequency | 1000Hz+/-2% |
| Total harmonic distortion | <3% |
| Reference conditions | Temperature 23°C (73°F) Static pressure 101.325kpa Relative humidity 50% |
| Accuracy of sound pressure level | Understated reference environment conditions +/- 0.5dB |
| Battery type | One 9V battery 006P |
| Battery test | Operate: Green LED indicator Low battery: Red LED indicator |
| Battery life | Approx. 40hours |
| Dimensions | 113mm(L) X 63mm(W) X 44mm(H) |
| Weight | Approx. 170g |
| Operating temperature | 0°C to 40°C |
| Storage temperature | -10°C to 60°C |
| Accessories | 9V battery, carrying case, instruction manual, 1/2inch microphone adapter. |

CENTER[®]
CENTER TECHNOLOGY CORP.

Importør:
Impex Produkter AS
Gamle Drammensvei 107
1363 HØVIK
Tel. 22 32 77 20
info@impex.no
www.impex.no