

TES-1350A Sound Level Meter



FEATURES

- 0.1dB Resolution
- Maximum hold function
- AUX OUTPUT JACKS



SPECIFICATION



Standard applied	IEC 651 Type2
Range	A LO (Low) - Weighting: 35- 100dB A HI (High) - Weighting: 65-130dB C LO (Low) - Weighting: 35- 100dB C HI (High) - Weighting: 65-130dB
Resolution	0.1dB
Frequency Range	31.5Hz to 8KHz
Accuracy	±2dB
Dynamic Range	65dB
Frequency Weighting	A 、 C
Time Weighting	Slow & Fast
Maximum Hold	Decay < 1dB/3min
Microphone	Electret condenser microphone
Calibration	Electrical calibration by using the internal oscillator (1KHz sine Wave at 94dB)
Auxiliary Output	AC conditioned, 0.65Vrms corresponding to each range step, impedance: 600 W DC conditioned, 10mV/dB (nominally)
Operating Condition	0°C to 40 °C < 80% R. H.
Storage Condition	-10°C to 60 °C < 70% R.H.
Display	3 1/2 digitals
Power Supply	one 9V battery
Size	240mm(L)x68mm(W)x25mm(H)
Weight	210g
Accessories	Instruction Manual, 9V Battery, Carrying Case, Screwdriver, Windscreen.