

Impex Produkter AS Gamle Drammensvei 107

1363 **HØVIK** Tel. 22 32 77 20 info@impex.no www.impex.no

METAL FINDER

MetalliScanner[®]



SPECIFICATIONS

8.87 in. H x 3.84 in. W x 2.23 in. D Dimensions

(225 mm x 98 mm x 57 mm) 10.1 oz. (286 g) without battery

Battery Type 9-V alkaline (not included)

Position Center of #4 (1/2 in.) rebar or 1/2 in.

Accuracy (13 mm) copper pipe at a minimum grid spacing of 6 in. (152 mm)

typically within 1/2 in. (13 mm)

Depth Up to 6 in. $(152 \text{ mm}) \pm 1 \text{ in. } (25 \text{ mm})$

Operating 20° to 120°F (-7° to 49°C) Temperature

Storage **Temperature**

Weiaht

-20° to 150°F (-29° to 66°C)

Humidity

80% RH (noncondensing)

Water

Splash and water resistant,

Resistance not waterproof

Impex Produkter AS

Verkseier Furulunds vei 15 0668 OSLO Tel. 22 32 77 20 Fax 22 32 77 25 info@impex.no www.impex.no

Electronic Metal Locator

Locate embedded metal before your drill bit or saw blade does. This powerful dedicated metal scanning tool can locate metal up to 6 inches deep in solid concrete.

MetalliScanner® MT 6 locates both ferrous and non-ferrous metal up to 6 inches (152 mm) deep in concrete and other non-metallic surfaces. It also differentiates between ferrous and non-ferrous metal targets and indicates the target depth in inches and centimeters.

MT 6 indicates when you are approaching a metal object with a large plus (+) sign on the display. When the plus becomes a minus (-), you have crossed over the target and are now moving away.

Use MetalliScanner® MT 6 to find or avoid rebar, cables, pipe, nails in reclaimed wood, nails/tacks in studs behind lath & plaster walls, electrical boxes and conduit, and more.

MetalliScanner® MT 6 is the tool recommended by the My Safe Florida Home Program to assist in hurricane loss mitigation.

- Automatically differentiates between magnetic metal (such as rebar) and non-magnetic metal (such as copper pipe)
- Shows the depth of metal from the surface in both inches and centimeters
- Easy-to-read LCD screen pinpoints the location of metal objects to the nearest ½ inch (13 mm) and depth to the nearest inch (25 mm)
- Helps map out the grid of metal through any nonmetallic construction material, including concrete, tile, and marble





©2009. MetalliScanner and Zircon are trademarks or registered trademarks of Zircon Corporation • C/N 1866 08/09