

KERN GAB30K0.2N

Checkweighing and portioning scale, also with EC type approval [M]



Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0 °C
Minimum humidity:	0 %

Power supply

Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adaptor included:	CH EURO UK

n/a: Mains adapter external

Power supply

Operating time (Backlight off):	90 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern

Service

DAkKS Certificate: 963-128

Category

Brand:	KERN
Category:	Balances
Product Group:	Bench scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	450 x 375 x 210 mm
Gross weight:	4,300 kg
Net weight:	3 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	320 x 330 x 125 mm
Dimensions of display device (WxDxH):	320 x 350 x 125 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	320 x 350 x 125 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

Measuring system

Adjustment options:	External calibration
Linearity:	600 mg
Readability [d]:	200 mg
Recommended adjusting weight:	20 kg (F1); 10 kg (F1)
Repeatability:	200 mg
Resolution:	150000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	g kg

Display

Display digit height: 2,400 cm

Counting

Counting resolution:	150000
Minimum piece weight at piece counting (Laboratory):	200 mg
Minimum piece weight at piece counting (Normal):	2 g

Functions

Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Weighing with tolerance range:	yes

KERN GAB30K0.2N



Checkweighing and portioning scale, also with EC type approval [M]

Piktogramme

STANDARD



OPTION



FACTORY

