visocolor® ECO Alkalinity TA



Test kit for the photometric determination of total alkalinity (acid capacity)

Method:

Alkalinity (acid capacity/acid binding capacity) describes the capability of water to neutralize acids with a pH range up to 4.3. The capability results from the sum of all bases (hydroxide ions) and buffers (carbonates, phosphates, etc.). The photometric determination of alkalinity uses bromophenol blue as an indicator.

Measurement range:

0.4-17.5 °e

5-250 mg/L CaCO₃

Contents:

sufficient for 100 tests

23 mL TA- 1

2 x 50 NANOFIXTA-2 1 syringe 5 mL

- 1 syringe 1 mL
- 2 tips for syringe 1 mL
- 1 instruction leaflet

Hazard warning:

Information regarding safety can be found on the box' labe and in the safety data sheet. You can download the SDS from www.mn-net.com/SDS.

Procedure:

Required equipment: Test tubes 16 mm OD (REF 91680)

- Rinse test tube several times with the test sample and fill with 5 mL sample (syringe 5 mL).
- Place test tube in the photometer and measure ZERO.
 Add 0.2 mL TA-1 (syringe 1 ml + syringe tip)
- Add 0.2 mL TA-1 (syringe 1 mL + syringe tip)
 Add 1 NANOFIX TA-2, close and shake vigorously.
- 5. Clean outside of the test tube and measure after 2 min.
- 6. Rinse and close the tubes after use. The method can be applied

also for the analysis of sea water.

To achieve more accurate results, the usage of pipettes is recommended.

Measurement:

see $\mathit{VISOCOLOR}^{\$}$ ECO test instructions for compact photometers PF-3/PF-12 $^{\mathit{Plus}}$

Conversion table:

°d	°e	°f	mg/L CaCO ₃	mmol/L H ⁺	gpg
1	1.3	1.8	18	0.36	1
2	2.5	3.6	36	0.72	2
3	3.8	5.4	54	1.08	3
4	5.0	7.1	71	1.42	4
5	6.3	8.9	89	1.78	5
6	7.5	10.7	107	2.14	6
7	8.8	12.5	125	2.50	7
8	10.0	14.3	143	2.86	8
9	11.3	16.1	161	3.22	9
10	12.5	17.8	178	3.56	10

Sample disposal:

Information regarding disposal can be found in the safety data sheet. You can download the SDS from www.mn-net.com/SDS.

Storage:

Store the test kit in a cool (< 25 °C) and dry place.