

# KERN EOS 150K-2

Wireless parcel and veterinary scales for flexible use in industry and practice



## Construction

Dimension display device (W×D×H)	210×110×45 mm
Dimensions weighing surface (W×D)	900×550 mm
Dimensions weighing surface	900×550 mm
Dimensions weighing platform (W×D×H)	900×550×60 mm
Material housing	plastic
Material weighing plate	stainless steel
Material platform	metal, lacquered, with black mat
Material display housing	plastic
Levelling feet adjustable	✓
Wall mount	✓

## Functions

Function for averaging under unstable weighing conditions	✓
Range of radio module	10 m
IP protection - complete device	-
IP protection - display	no IP protection
IP protection - platform	no IP protection
IP protection - load cell	no IP protection
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
	3 min
Auto-off interval(s) in mains power mode	4 min
	5 min
	2 min
Tare function	manual (multi)
Number of keys for operation	5

## Power Supply

Supplied power supply	Power supply & battery function (battery not included)
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO CH
Plug-in power supply / adapter for countries - optional	EURO CH
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Power socket for mains adapter	Hollow plug, inside minus, outside Ø 5,5 mm, inside Ø 2,1 mm, long 11,5 mm

## Category

Brand	KERN
Product category	Industrial scale
Product group	Platform scale
Product family	EOS-A

## Measuring System

Weighing system	Strain gauge
Weighing capacity [Max]	150 kg
Readability [d]	0,05 kg
Reproducibility	0,05 kg
Linearity	± 0,15 kg
Resolution	3.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	150 kg (M2)
Possible calibration points	150 kg
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,25 kg
Construction type of the scale	Single-range balance
Units	kg lb
Maximum creep (15 minutes)	200 g
Maximum creep (30 minutes)	400 g
Default unit	kg

## Display

Display type	LCD
Display backlight	no
Display screen size	100×35 mm
Display digit height	25 mm
Languages of the user interface	English Symbol language

# KERN EOS 150K-2



Wireless parcel and veterinary scales for flexible use in industry and practice

Battery / accumulator type Alkali(-Manganese)

Battery 6×1.5 V AA

Battery connection Battery insert

Battery operating time 70 h

## Environmental conditions

Ambient temperature [Min] 10 °C

Ambient temperature [Max] 35 °C

Humidity of environment [Max] 80 %

## Approval

CE mark ✓

## Services (optional)

Article number for adjustment at the location of installation 961-249

Article number for DAkkS calibration 963-129

Article number for certificate of conformity 969-517

## Packing & Shipping

Delivery time 1 d

Dimensions packaging (W×D×H) 1115×660×100 mm

Shipping method Parcel service

Net weight approx. 20 kg

Gross weight approx. 26 kg

Shipping weight 25,1 kg

## Product information

GTIN/EAN number 4045761488649

Trade number 84238220

REACH classification no prohibited substances

## Pictograms

### STANDARD



### OPTION

