

KERN DE 15K0.2D

The long-time success story with dust and spray protected display device



Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	9 V Block
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	CH EURO UK US

n/a:	Mains adapter external
------	------------------------

Power supply

Operating time:	12 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate:	963-128
--------------------	---------

Category

Brand:	KERN
Category:	Balances
Product Group:	Platform scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	530 x 417 x 160 mm
Gross weight:	8,700 kg
Net weight:	4 kg
Shipping method:	Parcel service

Construction

Cable length of display device:	1 m
Dimensions of display device (WxDxH):	225 x 110 x 45 mm
Dimensions of weighing plate (WxDxH):	318 x 308 x 90 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	315 x 305 mm

Measuring system

Adjustment options:	External calibration
Linearity:	800 mg 2000 mg
Readability [d]:	200 mg 500 mg
Recommended adjusting weight:	15 kg (F2)
Repeatability:	200 mg 500 mg
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2,500 s
Tare range:	15 kg
Warm up time:	2 h 2 h
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	dwt g kg lb mo oz ozt tl (HK) tl (Tw) tol

Display

Display digit height:	2,500 cm
-----------------------	----------

Counting

Counting resolution:	37500
Minimum piece weight at piece counting (Laboratory):	400 mg
Minimum piece weight at piece counting (Normal):	4 g

Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes

KERN DE 15K0.2D



The long-time success story with dust and spray protected display device

Piktogramme

STANDARD



OPTION

