## KERN IFT100K-3L



KERN Easy-Touch platform scale â the intuitive way to weigh - now also as high resolution version with high-resolution display



Measuring system			
Adjustment options:	External calibration		
Linearisation (points):	2		
Linearity:	15 g		
Readability [d]:	5 g		
Recommended adjusting weight:	150 kg (F2)		
Repeatability:	5 g		
Resolution:	30000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-150 kg		
Warm up time:	20 min		
Weighing capacity [Max]:	150 kg		
Weighing system:	Strain gauge		
Weighing units:	g kg		
Display			
Display digit height:	1,200 cm		
Display digit height:	1,200 cm		
Counting			
Counting resolution:	30000		
Mininum piece weight at piece counting (Laboratory:	5 g		

50 g

yes

Mininum piece weight at piece

counting (Normal): Reference weight:

Functions				
Capacity display:	yes			
Counting function:	yes			
Data hold function:	yes			
Function to save totals:	yes			
Help function on the display:	yes			
Peak function:	yes			
Percentage determination:	yes			
PRE-TARE function:	yes			
Standby function:	yes			
Time display:	yes			
Vibration-free weighing (Animal	yes			
weighing program):				
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0%			
-				
Power supply				
Charging time:	12 h			
Input voltage:	110 V - 230 V AC			
Mains adapter/adapter included:	CH EURO UK US			
mane adapter/adapter meradea.				
n/a:	Mains adapter external			
n/a:				
n/a: Power supply	Mains adapter external			
n/a: Power supply Operating time (Backlight on): Rechargeable battery:	Mains adapter external 7 h			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service	Mains adapter external 7 h Rchrg. battery optional			
n/a: Power supply Operating time (Backlight on): Rechargeable battery:	Mains adapter external 7 h Rchrg. battery optional			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation	Mains adapter external 7 h Rchrg. battery optional h: 961-249			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service	Mains adapter external 7 h Rchrg. battery optional			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation	Mains adapter external 7 h Rchrg. battery optional h: 961-249			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate:	Mains adapter external 7 h Rchrg. battery optional h: 961-249			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category	Mains adapter external 7 h Rchrg. battery optional n: 961-249 963-129			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand:	Mains adapter external 7 h Rchrg. battery optional n: 961-249 963-129 KERN			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group:	Mains adapter external 7 h Rchrg. battery optional n: 961-249 963-129 KERN Balances			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping	Mains adapter external 7 h Rchrg. battery optional n: 961-249 963-129 KERN Balances Industiral scale			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery:	Mains adapter external 7 h Rchrg. battery optional n: 961-249 963-129 KERN Balances Industiral scale 48 h			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Mains adapter external          7 h         Rchrg. battery optional			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Mains adapter external          7 h         Rchrg. battery optional         0: 961-249         963-129         KERN         Balances         Industiral scale         48 h         1000 x 700 x 260 mm         23 kg			
n/a: Power supply Operating time (Backlight on): Rechargeable battery: Service Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Mains adapter external          7 h         Rchrg. battery optional			

# KERN IFT100K-3L



KERN Easy-Touch platform scale â the intuitive way to weigh - now also as high resolution version with high-resolution display

Construction			
Cable length:	2,500 m		
Cable length of display device:	3 m		
Casing material:	Plastic		
Dimensions of display device (WxDxH):	252 x 152 x 133,4 mm		
Dimensions of weighing plate (WxDxH):	650 x 500 x 142 mm		
Level indicator:	yes		
Material weighing plate:	stainless steel		
Overall dimensions mounted (WxDxH):	460 x 240 x 360 mm		
Revolving screw feet:	yes		
Wall mount:	yes		
Weighing surface (WxD):	650 x 500 mm		

## Piktogramme

### STANDARD

CAL EXT	MEMORY	RS 232		KCP Protocol	and the second second	GLP INTERN	PCS	
% Percent	UNIT	-√+ ⊙ TOL	MOVE	000 IP 65	B H	DMS	1 DAY	

#### OPTION

	DAkkS
ACCU	+3 DAYS