# SAUTER SO 200K



### Photometer for precise light measurement up to 200,000 Lux



Category	
Brand	Sauter
Product categoriy	Environment/ Occupational safety
Product group	Light measuring instrument
Product family	SO
Measuring System	

Measuring head measuring frequency	2 Hz
Sound level meter sensor type	Silicone diode
Measuring range [Max] (Lux)	200 lx; 2000 lx; 20000 lx; 200000 lx
Readability illumination [d] (lx)	0,1 lx; 1 lx; 10 lx; 100 lx
Units	lx fc

## Display

Display type
Display digit height

## Construction

Dimension housing (W×D×H)	100×55×25 mm
Dimensions device (W×D×H)	100×55×25 mm
Dimension display device (W×D×H)	160×72×40 mm
Material housing	plastic
Material display housing	plastic
Cable length	1 m

LCD

√ √

16 mm

#### Functions

Hold function Peak function Auto-off interval(s) in battery mode/rechargeable battery mode 1 min

Power Supply	
Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery	9 V block
Battery connection	9V Bloc
Battery voltage	9 V
Environmental conditions	
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C
Approval	
CE mark	✓
Services (optional)	
Services (optional) Article number for factory calibration	961-190
Article number for factory	961-190
Article number for factory calibration	961-190 1 d
Article number for factory calibration Packing & Shipping	
Article number for factory calibration Packing & Shipping Delivery time	1 d
Article number for factory calibration Packing & Shipping Delivery time Dimensions packaging (W×D×H)	1 d 205×165×55 mm
Article number for factory calibration Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method	1 d 205×165×55 mm Parcel service
Article number for factory calibration Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method Net weight approx.	1 d 205×165×55 mm Parcel service 0,25 kg

#### STANDARD



#### OPTION

