
KERN IOC300K-3







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	25 g 50 g
Linearisation (points):	3
Linearity:	15 g 30 g
Load cell connection:	6-wire
Readability [d]:	5 g 10 g
Recommended adjusting weight:	300 kg (M1)
Repeatability:	5 g 10 g
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	2h 2h
Weighing capacity [Max]:	150 kg 300 kg
Weighing system:	Strain gauge
Weighing units:	oz PCS kg g lb tJ HJ

Display		
Display digit height (large):	2,500 cm	
Display digit height (small):	2,500 cm	
Technical data about verification		

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	10 g	
Mininum piece weight at piece counting (Normal):	100 g	

1 kg | 2 kg

Minimum load [Min]:

Functions		
Counting function:	yes	
Percentage determination:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	3 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	AUS US UK EURO CH
Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional

Services (optional)	
Adjustment at the location of installation: 961-249	

DAkkS Certificate: 963-129

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	1050 x 740 x 175 mm
Gross weight:	24,720 kg
Net weight:	21,900 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	650 x 500 x 150 mm

KERN IOC 300K-3



All-round platform scale with a range of communication options and EC type approval [M]

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 650 x 500 mm

Piktogramme

STANDARD



OPTION



FACTORY

