

The PDM PRO CO<sub>2</sub> is a single gas sustainable gas monitor designed to detect Carbon Dioxide (CO<sub>2</sub>) in the ambient environment. The PDM PRO CO<sub>2</sub> is sustainable, hence its battery and sensor can be replaced. When the device is turned on, the PDM PRO CO<sub>2</sub> continuously monitors ambient air for the presence of CO<sub>2</sub> and alerts the user to potentially unsafe exposure with LED, vibrating and audible alarms. After use the instrument can be turned off. With an excellent battery life of 14 days and a recharge time of only 100 minutes, the PDM PRO CO<sub>2</sub> offers great versatility for any user.

The PDM PRO CO<sub>2</sub> is easy to wear. It is fitted with a strong metal clip to conveniently secure it to a shirt, belt or helmet. The fully-fledged data logging means readings are stored at one-minute intervals for future reference. The PDM PRO CO<sub>2</sub> is easy to manually bump test and calibrate.

### Key Features

- Rugged, durable, impact-proof housing
- 14 days of battery life, full recharge in 100 minutes
- Event log that stores 30 most recent events
- Data log with a capacity of up to 64,000 data points
- Replaceable battery and sensor



### Application Examples

- Food and beverage industries
- Laboratories
- Health Science
- Refrigeration
- Packaging industry
- Greenhouse facilities

## DETECTOR SPECIFICATIONS

<b>Size</b>	54(W) x 99,5(H) x 38(D) mm
<b>Weight</b>	135 grams
<b>Sensor technology</b>	Non-dispersive Infrared (NDIR)
<b>Temperature</b>	-20°C ~ +50°C
<b>Humidity</b>	5% ~ 95% RH (non-condensing)
<b>Alarm types</b>	High Alarm, Low Alarm, TWA Alarm, STEL Alarm, Over range Alarm, Battery low warning, Calibration due warning
<b>Alarm signal</b>	Acoustic: 90dB @ 10cm Visual: Red flashing LED's Vibration: Vibration alarm
<b>Display</b>	LCD Display
<b>Calibration</b>	Manual 2-point calibration
<b>Datalog</b>	Stores up to 64000 datapoints
<b>Event log</b>	30 Most recent events (overwriting)
<b>Operating time</b>	14 days
<b>Battery charging time</b>	100 minutes
<b>Measuring range</b>	0-5%vol CO <sub>2</sub> or 0-50000ppm CO <sub>2</sub>
<b>Sensor resolution</b>	0.01 vol% or 100 ppm
<b>Housing</b>	Rubber enclosed polycarbonate
<b>IP-Rating</b>	IP67
<b>Response Time T<sup>90</sup></b>	≤ 60sec
<b>EMI/RFI</b>	EMC directive (2014/30/EU)
<b>Sensor Life</b>	5 years (expected)
<b>Safety certifications</b>	<b>ATEX:</b> Non-ATEX <b>CE:</b> 2014/30/EU RoHS 2
<b>Warranty</b>	24 Months factory warranty
<b>Included accessories</b>	Calibration Cap USB-C charger (Usable worldwide) User Manual Factory calibration certificate

### SENSOR SPECIFICATIONS

Sensor	Detectable Gas Ranges	Resolution	Article Number
WatchGas PDM Pro CO <sub>2</sub> NDIR sensor	0-5%vol CO <sub>2</sub> 0-50000ppm CO <sub>2</sub>	0.01 %vol 100 ppm	7192008

### ORDER INFORMATION FOR ACCESORIES

Description	Article Number
WatchGas Last-O-More Gas Sampling Hose 5x8mm	7SOL-411-0018-039
WatchGas Sampling Pump	7177202
WatchGas Fixed Flow Regulator 0.5l/min	CAL-A0195339
Calibration cap for WatchGas PDM	7177200



