

TPWI-PRO-EX2GD

TPWI-PRO series "EX" 2GD PALLET TRUCK SCALE IN STAINLESS STEEL ZONE 1/21 & 2/22



AISI 304 stainless steel pallet truck scale for use in ATEX hazardous areas 1 & 21 & 2 & 22, with Ex II 2G IIB T4 Gb X and Ex II 2D IIIC T197°C Db X protection modes. Available in approved version for legal-for-trade use. Manufactured, calibrated and adjusted in Italy by Dini Argeo, using certified sample masses.

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Maximum lifting capacity: 2.000 kg; special capacities on request, up to 3.000 kg.
- Resolution:
 - > internal use: 0,2 / 0,5 kg
 - > approved: 0,5 / 1 kg
- Accuracy (weighing of goods on Europallet with distributed load):
 - > internal use: +/- 1 kg
 - > approved: according to CE certification (Directive 2014/31/EU)
- Calibration and Set-Up parameters configurable from keyboard.

WHY CHOOSE TPWI-PRO serie EX 2GD

- Pallet truck scale with thick stainless steel structure, entirely manufactured in Italy.
- Lifting pump manufactured entirely in Italy, available on request for lifting up to 3,000 kg.
- Made with ATEX certified Dini Argeo components.
- Weight indicator with waterproof casing in IP65 STAINLESS STEEL, easy to clean and resistant in harsh and corrosive environments.
- The large 25mm LCD display allows viewing even in low light conditions.
- Available in approved version for legal-for-trade use.
- Extractable battery, rechargeable in safe area, connectable and disconnectable to the weighing system even in hazardous area.
- Autonomy of 150 hours approximately, or 24/7 with optional second rechargeable battery.
- Fitted with 4 Dini Argeo ATEX certified IP68 stainless steel load cells.
- Each pallet truck is tested and supplied with calibration certificate to guarantee the declared accuracy.
- Special non-standard dimensions available on estimate.

TECHNICAL FEATURES

- Low-profile forks, only 85 mm.
- Fork dimensions 1150 x 550 x 85 mm.
- Lifting range: from 85 to 205 mm.
- Pallet truck weight: 135 kg approx.
- Supporting structure made entirely of extra-thick AISI 304 stainless steel.
- Forks in AISI 304 stainless steel.
- Closed fork covers for increased protection of the double load wheels.
- Antistatic guide wheels, with polyurethane coating for smooth running. 200 mm diameter ensures optimum smoothness and manoeuvrability.
- Antistatic loading rollers.
- Lifting pump in AISI 304 stainless steel.
- Waterproof membrane keyboard, with 17 numeric/functional keys.
- Dini Argeo electronics, ATEX certified, intrinsically safe.
- Standard 110/230Vac 50Hz battery charger with EU, UK, US and AU plugs (recharge time 8 hours).
- Temperature range: -10° / +40° C

THE EASIEST ONE TO RECALIBRATE AND REPAIR

- The only one without junction box: the adjustment of each single load cell is conveniently carried out from the keyboard.
- Spare parts and wearing parts always available and ready for delivery.
- Specialized service centers throughout Italy.

MAIN FUNCTIONS

- Zeroing, Tare
 - High resolution display x 10.
 - Net/Gross or lb/kg conversion.
 - Weights totalisation.
 - Formulation.
- Discover the other functions, download the manual.

OTHER AVAILABLE VERSIONS

- Other capacities / special resolutions: upon request.
- Other special versions: upon request.

TAILORED SIZES FOR EVERY NEED

- TPWI-PRO "EX" 2GD can be manufactured with special fork dimensions:
 - Lengths from 800 up to 2200 mm (up to 1800 mm in approved version)
 - Widths from 400 up to 900 mm (up to 680 mm in approved version)

DETAIL 1



Extractable battery

VERSIONS

Available versions

	Codice	Max (kg)	d (kg)	M (kg)
	TPWI-PRO-EX2GD	1000 / 2000	0,2 / 0,5	--
	TPWIM-PRO-EX2GD M	1000 / 2000	--	0,5 / 1



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

**DINI ARGEO
FRANCE sarl**
France

**DINI ARGEO
GMBH**
Germany

**DINI ARGEO
UK Ltd**
United Kingdom

**DINI ARGEO WEIGHING
INSTRUMENTS Ltd**
China

**DINI ARGEO
OCEANIA**
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE