KERN EOC100K-2



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

| Adjustment options: | External calibration | | | |
|---|----------------------|--|--|--|
| Linearisation (points): | 3 | | | |
| Linearity: | 60 g 150 g | | | |
| Load cell connection: | 4-wire | | | |
| Readability [d]: | 20 g 50 g | | | |
| Recommended adjusting weight: | 150 kg (M1) | | | |
| Repeatability: | 20 g 50 g | | | |
| Resolution: | 3 3.000 | | | |
| Stabilisation time under laboratory conditions: | 2 s | | | |
| Tare range: | 150 kg | | | |
| Warm up time: | 10 min | | | |
| Weighing capacity [Max]: | 60 kg 150 kg | | | |
| Weighing system: | Strain gauge | | | |
| Weighing units: | oz kg PCS g lb | | | |

Display

| Display digit height (large): | 2,500 cm |
|-------------------------------|----------|
| Display digit height (small): | 2,500 cm |

Counting

| e e e e e e e e e e e e e e e e e e e | |
|---|-------|
| Counting resolution: | 30000 |
| Mininum piece weight at piece counting (Laboratory: | 5 g |
| Mininum piece weight at piece counting (Normal): | 50 g |

Functions

| Counting function: | yes | |
|--|-----|--|
| Percentage determination: | yes | |
| Vibration-free weighing (Animal weighing program): | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | | | | | |
|--|---|--|--|--|--|
| | 00.0/ | | | | |
| Maximum humidity: | 80 % | | | | |
| Maximum operating temperature: | 40 °C | | | | |
| Minimum ambient temperature: | -10 °C | | | | |
| Minimum humidity: | 0 % | | | | |
| Power supply | | | | | |
| Charging time: | 3 h | | | | |
| Input voltage: | 100V-240V 0.4A | | | | |
| Mains adapter: | Mains adapter external | | | | |
| Mains adapter/adapter included: | CH UK EURO | | | | |
| Operating time: | 100 h | | | | |
| Operating time (Backlight off): | 43 h | | | | |
| Operating time (Backlight on): | 26 h | | | | |
| Rechargeable battery: | Rchrg. battery optional - intern | | | | |
| Services (optional) | | | | | |
| Adjustment at the location of installation | n: 961-249 | | | | |
| DAkkS Certificate: | 963-129 | | | | |
| Category | | | | | |
| Brand: | KERN | | | | |
| Category: | Balances | | | | |
| Product Group: | Industiral scale | | | | |
| | | | | | |
| Packaging & shipping | | | | | |
| Packaging & shipping Delivery: | 24 h | | | | |
| | 24 h 712 x 365 x 200 mm | | | | |
| Delivery: | | | | | |
| Delivery: Dimensions packaging (WxDxH): | 712 x 365 x 200 mm | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: | 712 x 365 x 200 mm 7,980 kg | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: | 712 x 365 x 200 mm 7,980 kg 5,200 kg | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction | 712 x 365 x 200 mm 7,980 kg 5,200 kg | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device | 712 x 365 x 200 mm 7,980 kg 5,200 kg Parcel service | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): | 712 x 365 x 200 mm 7,980 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: | 712 x 365 x 200 mm 7,980 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: | 712 x 365 x 200 mm 7,980 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate: | 712 x 365 x 200 mm 7,980 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel | | | | |
| Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: | 712 x 365 x 200 mm 7,980 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes | | | | |

KERN EOC100K-2



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

| | • 888.• | KCP | GLP | | % | + ③ ③) | ^- |
|---------|---------|----------|---------|-----|---------|-----------|------|
| CAL EXT | RS 232 | PROTOCOL | PRINTER | PCS | PERCENT | | MOVE |
| 666 | | | | | | | |
| IP 65 | MULTI | DMS | 1 DAY | | | | |

OPTION

|) | DAkkS |
|-----------|---------|
| ACCU | +3 DAYS |