KERN EOC 20K-3A



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

| 0, | | | |
|---|----------------|--|--|
| Adjustment options: External calibration | | | |
| Linearisation (points): | 3 | | |
| Linearity: | 6 g | | |
| Load cell connection: | 4-wire | | |
| Readability [d]: | 2 g | | |
| Recommended adjusting weight: | 24 kg (M1) | | |
| Repeatability: | 2 g | | |
| Resolution: | 12000 | | |
| Stabilisation time under laboratory conditions: | 2 s | | |
| Tare range: | 24 kg | | |
| Warm up time: | 30 min | | |
| Weighing capacity [Max]: | 24 kg | | |
| Weighing system: | Strain gauge | | |
| Weighing units: | oz kg PCS g lb | | |

Display

| Display digit height (large): | 2,500 cm |
|-------------------------------|----------|
| Display digit height (small): | 2,500 cm |

Counting

| Counting resolution: | 24000 |
|---|-------|
| Mininum piece weight at piece counting (Laboratory: | 1 g |
| Mininum piece weight at piece counting (Normal): | 10 g |

Functions

| Counting function: | yes | |
|--|-----|--|
| Percentage determination: | yes | |
| Vibration-free weighing (Animal weighing program): | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | | | |
|--|-------------------------------------|--|--|
| Maximum humidity: | 80 % | | |
| Maximum operating temperature: | 40 °C | | |
| Minimum ambient temperature: | -10 °C | | |
| Minimum humidity: | 0 % | | |
| Power supply | | | |
| Charging time: | 3 h | | |
| Input voltage: | 100V-240V 0.4A | | |
| Mains adapter: | Mains adapter external | | |
| Mains adapter/adapter included: | CH UK EURO | | |
| Operating time: | 100 h | | |
| Operating time (Backlight off): | 43 h | | |
| Operating time (Backlight on): | 26 h | | |
| Rechargeable battery: | Rchrg. battery optional - intern | | |
| Services (optional) | | | |
| Adjustment at the location of installation | n:961-248 | | |
| DAkkS Certificate: | 963-128 | | |
| Category | | | |
| Brand: | KERN | | |
| Category: | Balances | | |
| Product Group: | Industiral scale | | |
| Packaging & shipping | | | |
| Delivery: | 24 h | | |
| Dimensions packaging (WxDxH): | 715 x 360 x 185 mm | | |
| Gross weight: | 7,500 kg | | |
| Net weight: | 5,200 kg | | |
| Shipping method: | Parcel service | | |
| Construction | | | |
| Cable length of display device: | 3 m | | |
| Dimensions of display device (WxDxH): | 268 x 115 x 80 mm | | |
| Dimensions of weighing plate (WxDxH): | 300 x 300 x 110 mm | | |
| of stand: | 33 cm | | |
| Level indicator: | yes | | |
| Material weighing plate: | stainless steel | | |
| Revolving screw feet: | yes | | |
| |) e e | | |
| Wall mount: | yes | | |

KERN EOC 20K-3A



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

| CAL EXT | • ###A • RS 232 | KCP Protocol | GLP PRINTER | PCS | SUM | % Percent | -√+ ⊙ うッ TOL | MOVE |
|------------|--------------------|--------------------|----------------|-----|-----|--------------|--------------------|------|
| 666 | _ | all and the second | • • | | | | | |
| IP 65 | MULTI | DMS | 1 DAY | | | | | |

OPTION

|) | DAkkS | | |
|-----------|---------|--|--|
| ACCU | +3 DAYS | | |