KERN EOC 30K-3L



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	15 g 30 g
Load cell connection:	4-wire
Readability [d]:	5 g 10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g 10 g
Resolution:	3 3.500
Stabilisation time under laboratory conditions:	2 s
Tare range:	35 kg
Warm up time:	10 min
Weighing capacity [Max]:	15 kg 35 kg
Weighing system:	Strain gauge
Weighing units:	oz kg PCS g lb

Display

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Counting

Counting resolution:	35000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Functions

Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Maximum numidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0Charging time:3 hInput voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)XAdjustment at the location of installation:963-128DAkkS Certificate:963-128DakkS Certificate:963-128Product Group:Industiral scalePackaging & shippingIndustiral scalePackaging & shipping875 x 485 x 150 mmGross weight:1,2500 kgNet weight:9 kgShipping method:9 kgShipping method:3 mDimensions of display device:3 mDimensions of display device:3 mDimensions of display device:3 mDimensions of weighing plate\$00 x 400 x 120 mm(WxDXH):00 x 400 x 120 mmof stand:33 cmLevel indicator:yesWall mount:yes	Environmental conditions				
Maximum operating temperature:40 °CMinimum ambient temperature:-10 °CMinimum humidity:0 %Power supply0 %Charging time:3 hInput voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Services (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128Parad:KERNCategoryBalancesProduct Group:Industiral scalePackaging & shipping875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstruction268 x 115 x 80 mm(WXDXH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Maximum humidity:	80 %			
Minimum ambient temperature:-10 °CMinimum humidity:0 %Power supplyCharging time:3 hInput voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time:26 hRechargeable battery:Rchrg. battery optional - internServices (optional)963-128DAkkS Certificate:963-128DAkkS Certificate:963-128Parand:KERNCategory:BalancesProduct Group:Industrial scalePackaging & shipping875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:9 kgDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):95 stainless steelLevel indicator:yesMaterial weighing plate:stainless stee		40 °C			
Power supplyCharging time:3 hInput voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128CategoryBalancesProduct Group:Industiral scalePackaging & shippingIndustiral scalePackaging & shipping875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:9 kgShipping method:268 x 115 x 80 mm(WxDxH):370 x 400 x 120 mm(WxDXH):00 x 400 x 120 mm					
Charging time:3 hInput voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128CategoryBalancesProduct Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceCable length of display device:3 mDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevel indicator:yes	Minimum humidity:	0 %			
Charging time:3 hInput voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128CategoryBalancesProduct Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceCable length of display device:3 mDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevel indicator:yes					
Input voltage:100V-240V 0.4AMains adapter:Mains adapter externalMains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)XAdjustment at the location of installation:961-248DAkkS Certificate:963-128DAkkS Certificate:963-128CategoryBalancesBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingYDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstruction268 x 115 x 80 mm(WxDxH):31 cmDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Power supply				
Mains adapter:Mains adapter externalMains adapter/adapter included:CH UK EUROOperating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation:963-128DAkkS Certificate:963-128CategoryBrand:KERNCategory:BalancesProduct Group:Industrial scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstruction268 x 115 x 80 mmCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Charging time:	3 h			
Mains adapter/adapter included:CH UK EUROOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128CategoryBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:9 kgShipping of display device:3 mDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:yesWiterial weighing plate:yes	Input voltage:	100V-240V 0.4A			
Operating time:100 hOperating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation:963-128DAkkS Certificate:963-128DAkkS Certificate:963-128CategoryBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:9 kgShipping method:3 mDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRecolving screw feet:yes	Mains adapter:	Mains adapter external			
Operating time (Backlight off):43 hOperating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation:961-248DAkkS Certificate:963-128DAkkS Certificate:963-128CategoryBalancesBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shipping24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceCable length of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRecharge from the service100 x 400 x 120 mm	Mains adapter/adapter included:	CH UK EURO			
Operating time (Backlight on):26 hRechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128Category963-128Brand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shipping10Delivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceCable length of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Operating time:	100 h			
Rechargeable battery:Rchrg. battery optional - internServices (optional)Adjustment at the location of installation: 961-248DAkkS Certificate:963-128DAkkS Certificate:963-128CategoryBalancesBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingIndustiral scaleDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstruction268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Operating time (Backlight off):	43 h			
intern Services (optional) Adjustment at the location of installation: 961-248 DAkkS Certificate: 963-128 Category Brand: KERN Category: Balances Product Group: Industiral scale Packaging & shipping Delivery: 24 h Dimensions packaging (WxDxH): 875 x 485 x 150 mm Gross weight: 12,500 kg Net weight: 9 kg Shipping method: Parcel service Construction Cable length of display device: 3 m Dimensions of display device: 3 m Dimensions of display device 268 x 115 x 80 mm (WxDxH): 0f stand: 33 cm Level indicator: yes Material weighing plate: stainless steel Revolving screw feet: yes	Operating time (Backlight on):	26 h			
Adjustment at the location of installation: 961-248DAkkS Certificate:963-128CategorySecond Second Se	Rechargeable battery:				
DAkkS Certificate:963-128CategoryBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstruction268 x 115 x 80 mm(WxDxH):30 x 400 x 120 mmDimensions of display device:3 mDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Services (optional)				
CategoryBrand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):Dimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cm12evel indicator:vesMaterial weighing plate:stainless steelRevolving screw feet:yes	Adjustment at the location of installation	n:961-248			
Brand:KERNCategory:BalancesProduct Group:Industiral scalePackaging & shippingIndustiral scalePackaging & shipping24 hDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstruction268 x 115 x 80 mmCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):Dimensions of weighing plateOf stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	DAkkS Certificate:	963-128			
Category:BalancesProduct Group:Industiral scalePackaging & shippingIndustiral scaleDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmOf stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Category				
Product Group:Industiral scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device:268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmDimensions of weighing plate30 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Brand:	KERN			
Packaging & shippingDelivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmOf stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Category:	Balances			
Delivery:24 hDimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmDimensions of weighing plate33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Product Group:	Industiral scale			
Dimensions packaging (WxDxH):875 x 485 x 150 mmGross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmOf stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Packaging & shipping				
Gross weight:12,500 kgNet weight:9 kgShipping method:Parcel serviceConstructionParcel serviceCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Delivery:	24 h			
Net weight:9 kgShipping method:Parcel serviceConstructionParcel serviceCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Dimensions packaging (WxDxH):	875 x 485 x 150 mm			
Shipping method:Parcel serviceConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):260 x 400 x 120 mmDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Gross weight:	12,500 kg			
ConstructionCable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):268 x 115 x 80 mmDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Net weight:	9 kg			
Cable length of display device:3 mDimensions of display device268 x 115 x 80 mm(WxDxH):500 x 400 x 120 mmDimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmof stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Shipping method:	Parcel service			
Dimensions of display device (WxDxH):268 x 115 x 80 mmDimensions of weighing plate (WxDxH):500 x 400 x 120 mmof stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Construction				
(WxDxH):Dimensions of weighing plate500 x 400 x 120 mm(WxDxH):33 cmof stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Cable length of display device:	3 m			
Dimensions of weighing plate500 x 400 x 120 mm(WxDxH):of stand:33 cmLevel indicator:yesMaterial weighing plate:stainless steelRevolving screw feet:yes	Dimensions of display device	268 x 115 x 80 mm			
Level indicator: yes Material weighing plate: stainless steel Revolving screw feet: yes	Dimensions of weighing plate (WxDxH):	500 x 400 x 120 mm			
Material weighing plate: stainless steel Revolving screw feet: yes	of stand:	33 cm			
Revolving screw feet: yes	Level indicator:	yes			
	Material weighing plate:	stainless steel			
Wall mount: yes	Revolving screw feet:	yes			
	Wall mount:	yes			

KERN EOC 30K-3L



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

	• 888. •	KCP	GLP			%	-√+ ⊙ ⋽ৢ৽	^-
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	SUM	PERCENT	TOL	MOVE
•••								
IP 65	MULTI	DMS	1 DAY					

OPTION

)	DAkkS
ACCU	+3 DAYS