

SAUTER JIT 200

Infrared thermometer for industry, environmental engineering and maintenance work

KERN



Category

Brand	Sauter
Product category	Environment/ Occupational safety
Product group	Infrared thermometer
Product family	JIT

Measuring System

Temperature - measuring range 1 [Min]	-32 °C
Temperature - measuring range 1 [Max]	0 °C
Temperature accuracy - measuring range 1	+/- 1,5 °C+0,1 °C/ °C
Temperature repeatability - measuring range 1	+/- 0,7 °C
Temperature coefficient - measuring range 1	+/- 0,1 °C/ °C
Temperature - measuring range 2 [Min]	0 °C
Temperature - measuring range 2 [Max]	100 °C
Temperature accuracy - measuring range 2	+/- 1,5 °C
Temperature repeatability - measuring range 2	+/- 0,7 °C
Temperature coefficient - measuring range 2	+/- 0,1 °C/ °C
Temperature - measuring range 3 [Min]	100 °C
Temperature - measuring range 3 [Max]	1020 °C
Temperature accuracy - measuring range 3	+/- 1,5%
Temperature repeatability - measuring range 3	+/- 0,7%

Temperature coefficient - measuring range 3	+/- 0,1%/ °C
Level of emission [Min]	0,1
Level of emission [Max]	1
D:S Optic	20:1
Response time	250 ms
Default unit	°C
Units	°C °F
Temperature [Min] (°C)	-32 °C
Temperature [Max] (°C)	1100 °C

Construction

Dimension (W×D×H)	179×127×53 mm
Material	plastic
Laser power	0,001 W
Laser class	2
Column mount possible	✓

Functions

Function for averaging	✓
Limit-setting function	✓
Hold function	✓
Peak function	✓
Memory function	✓
Statistic function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	15 sec

Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery	9 V block
Battery connection	9V Bloc
Battery operating time	9 h

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	225×150×70 mm
Shipping method	Parcel service
Net weight approx.	0,35 kg
Gross weight approx.	0,50 kg
Shipping weight	0,5 kg

SAUTER JIT 200

KERN

Infrared thermometer for industry, environmental engineering and maintenance work

Pictograms

STANDARD

