
SAUTER FC 1K-BT







| Category | |
|-------------------|-------------------|
| Brand | Sauter |
| Product categoriy | Force measurement |
| Product group | Concrete tester |
| Product family | FC |
| | |

| Measuring System | |
|---|------------------------|
| Measuring range force [Max] (N) | 1 kN |
| Readability force [d] (N) | 1 N |
| Measuring head measuring frequency | 1000 Hz |
| Overload protection (% of [Max]) | 150% |
| Tolerance (% of [Max]) | 0,3% |
| Internal data memory: Number of individual values | 500 |
| Directions of force | tension compression |
| Default unit | N |
| Number of platforms / channels | 1 |

| Display | |
|----------------------|---------|
| Display type | LCD |
| Display resolution | 160×128 |
| Display digit height | 10 mm |
| Screen reversible | ✓ |

| Construction | |
|---------------------------------------|--------------|
| Dimension housing (W×D×H) | 145×73×34 mm |
| Dimensions completely mounted (W×D×H) | 145×73×34 mm |
| Dimension display device (W×D×H) | 145×73×34 mm |
| Material housing | metal |
| Material display housing | metal |

| Mounting - force application | External thread M6 |
|------------------------------|--------------------|
| Load support (tensile force) | Hook |

| Functions | |
|--|------------|
| Limit-setting function | ✓ |
| Peak function | ✓ |
| Memory function | ✓ |
| Auto-off interval(s) in battery mode/rechargeable battery mode | 1 - 60 min |

| Interface | |
|------------|-------------------------------|
| Interfaces | RS-232 standard USB-Device |

| Power Supply | |
|---|----------------------|
| Supplied power supply | Accu & Power supply |
| Plug-in power supply type | Power adapter |
| Plug-in power supply / adapter for countries - included with the delivery | EURO CH |
| Plug-in power supply / adapter for countries - optional | UK US |
| Input voltage power supply / power [Max] | 100 V - 240 V |
| Input voltage device / power [Max] | 5 V, 1 A |
| Power socket for mains adapter | USB B |
| Battery / accumulator type | NiMH |
| Battery connection | 2-pole tub connector |
| Rechargeable battery operating time - backlight on | 20 h |
| Rechargeable battery operating time - backlight off | 20 h |
| Rechargeable battery charging time | 4 h |

| Approval | |
|--|---------|
| CE mark | ✓ |
| Services (optional) | |
| Article number for DAkkS calibration (tensile force) | 963-162 |
| Article number for DAkkS calibration (compressive force) | 963-262 |
| Article number for DAkkS calibration (tensile force/compressive force) | 963-362 |
| Article number for factory calibration | 961-162 |

1

SAUTER FC 1K-BT



Compact force measuring instrument

Article number for factory
calibration (tensile force)

Article number for factory
calibration (compressive force)

961-162

961-262

Article number for factory calibration (tensile force/ 961-362

compressive force)

Packing & Shipping Delivery time 1 d Dimensions packaging (W×D×H) 340×155×110 mm Shipping method Parcel service Net weight approx. 1,8 kg Gross weight approx. 2,0 kg Shipping weight 2 kg

Product information

GTIN/EAN number 4045761247802

Pictograms

STANDARD





OPTION

