SAUTER HO 5K



Premium UCI hardness testing device for Rockwell, Brinell and Vickers



Category	
Brand	Sauter
Product categoriy	Hardness testing
Product group	UCI hardness tester
Product family	НО

Measuring System	
Measuring range Rockwell - scale A	61-85,6HRA
Measuring range Rockwell - scale B	41-100HRB
Measuring range Rockwell - scale C	20,3-68HRC
Test object thickness [Min]	2 mm
Hardness scales	HV 5
Test object minimum weight [Min]	300 g
Test block inclusive	✓
Measuring range Brinell	79-618HB
Units	HL HV HB HRB HRC MPa HRA
Measuring range tensile strength	255-2180MPa
Measuring range Vickers	80-1599HV
Test force Hardness measurement	50 N
Measuring probe length	15,5 cm
Measuring probe diameter	18 mm

LCD graphic

Display

Display type

Construction	
Dimension (W×D×H)	28×83×160 mm
Dimension housing (W×D×H)	28×83×160 mm
Material housing	metal, lacquered
Type of drive	manual
Scale - Display type	Digital

Functions	
Function for averaging	✓
Limit-setting function	✓
360° measurement possible	✓
Memory function	✓
Memory - number of results	1.000
Statistic function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	30 min

Interface	
Interfaces	USB-Device

Power Supply	
Supplied power supply	Accu & Power supply
Plug-in power supply type	USB including power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	EURO AUS UK US
Input voltage power supply / power [Max]	110 - 240 V
Power supply cable removable	removable
Input voltage device / power [Max]	5 V, 2 A
Power socket for mains adapter	Micro USB
Battery / accumulator type	Li-lon
Battery connection	Connector pin
Battery capacity	3.200 mAh
Battery voltage	3,7 V
Battery - Number of cells	4
Battery – Individual weight	80 g
Battery – Total weight	320 g
Battery - Construction	Inseparable connection of cells (pack)
Battery capacity (Wh)	14,5 Wh
Battery - Lithium content	5 g

1

SAUTER HO 5K



Premium UCI hardness testing device for Rockwell, Brinell and Vickers

Rechargeable battery operating 6 h time - backlight on

Rechargeable battery operating 12 h time - backlight off

Rechargeable battery charging 8 h

not connected, isolated Battery/Accu connected in the device

Approval CE mark

Services (optional) Article number for factory 961-270 calibration

Packing & Shipping Delivery time 395×320×140 mm Dimensions packaging (W×D×H) Shipping method Parcel service Net weight approx. 0,95 kg Gross weight approx. 4,4 kg Shipping weight 4,37 kg

Product information GTIN/EAN number 4045761200661 **REACH classification** no prohibited substances

Pictograms

STANDARD



















OPTION

