

Easy Pesa 3GD Series, Stainless Steel Scales, for ATEX Zones 2 and 22



As of: Tuesday, December 2, 2025



Standard Features

Platform Features

- Approved “single point” stainless steel load cell according to OIML R60 standards with protection against dust and water splashes according to IP67 standards
- ATEX approved load cell with ATEX protection:
 - ATEX II 1G Ex ia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) Ga.
 - ATEX II 1D Ex ta IIIC TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C) Da IP65
- Structure, enclosure and loading plate made in AISI304 satin finish stainless steel
- Adjustable levelling feet with plastic over shoe

- Supplied with support column, height:
 - 500 mm in the "Q" models
 - 700 mm in the "X" models
- Length of connection cable to the indicator: 3m.

Weighing Indicator Features

- IP68 weight indicator for ATEX areas with protection methods according to:
 - ATEX II 3G Ex nR IIC T6 Gc X for gases
 - ATEX II 3D Ex tc IIIC T130°C Dc IP68 X for dust.
- EC-Type-Examination certificate according to Annex III (ATEX directive). CE-M approvable (OIML R-76 / EN 45501)
- Waterproof 17-key numerical and functional keyboard
- Backlight LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/d in CE-M approved version for legal for trade use
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. auto-select
- Power supply through external battery pack with 100h operating time. It's possible to buy another battery pack for continuous use (24/7)
- Charger included in the supply

Easy Pesa 3GD Series, Stainless Steel Scales, for ATEX zones 2 and 22 Specifications

Scale Function	Selectable Functioning Mode	Certifications
Zeroing	High Resolution Weighing x 10	The price includes the ATEX
Automatic tare	Net/Gross or lb/kg conversion	declaration of conformity
Presettable tare	Weight totalization	(DCATEX3GD) and the load cell
Selectable function command	Formula weighing	certificate of conformity
On/off switching	+/- Checkweighing	(CCATEX).
	Counting (Max. resolution of 1.500.000 divisions)	

Available Versions

Code	Plate Max (mm)	Max (kg)	d (kg)	<div>M</div> M (kg*)	<div>M</div> 2R (g)*	d HR (kg)*
EPQI3GD15B-1	400x400	15	2	5	2/5	1
EPQI3GD30B-1	400x400	30	5	10	5/10	2
EPQI3GD60B-1	400x400	60	10	20	10/20	5
EPQI3GD150B-1	400x400	150	20	50	20/50	10
EPXI3GD60B-1	600x600	60	10	20	10/20	5
EPXI3GD150B-1	600x600	150	20	50	20/50	10
EPXI3GD300B-1	600x600	300	50	100	50/100	20

(*) These divisions are obtainable only with the relative options.

Parts

Part #	Description
--------	-------------

Available Versions

EPQI3GD15B-1	ATEX 3GD bench scale, Max= 15kg, d= 2g. Ex II 3G IIC T6 Gc X and Ex II 3D IIIC T115°C Dc X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).
EPQI3GD30B-1	ATEX 3GD bench scale, Max= 30kg, d= 5g. EEx II 3G IIC T6 Gc X and Ex II 3D IIIC T115°C Dc X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).
EPQI3GD60B-1	ATEX 3GD bench scale, Max= 60kg, d= 10g. Ex II 3G IIC T6 Gc X and Ex II 3D IIIC T115°C Dc X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).
EPQI3GD150B-1	ATEX 3GD bench scale, Max= 150kg, d= 20g. Ex II 3G IIC T6 Gc X and Ex II 3D IIIC T115°C Dc X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).
EPXI3GD60B-1	ATEX 3GD bench scale, Max= 60kg, d= 10g. Ex II 3GD IIC T6 T115°C X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).
EPXI3GD150B-1	ATEX 3GD bench scale, Max= 150kg, d= 20g. Ex II 3GD IIC T6 T115°C X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).
EPXI3GD300B-1	ATEX 3GD bench scale, Max= 300kg, d= 50g. Ex II 3GD IIC T6 T115°C X protection. Multifunction weight indicator with stainless steel IP68 case, 17-key keypad and LCD display. Supplied with manuals and conformity declaration (available in IT, EN, FR, DE).

Options

Part #	Description
--------	-------------

Extractable additional battery

BP6ESTATEX3GD	IP65 stainless steel, external ATEX battery pack, for 2 and 22 zones. Marking: ATEX II 3G Ex ec IIC T6 Gc X for gas and ATEX II 3D Ex tc IIIC T85°C Dc IP65 X for dust. For Dini Argeo ATEX 3GD instruments. ATTENTION: rechargeable in safe zone only, connectable and disconnectable from the weighing system also in hazardous area. (Battery charger not included).
----------------------	---

Approval for Sale to Third Parties

ECM	Single range 3000e legal for trade approval, for single platform/scale. NOTE: Depending on the product, the ECM approval service may require DINICAL calibration service. Check to see if DINICAL is in the product options.
ECM2	Multi-range 3000+3000e legal for trade approval, for single platform/scale. NOTE: Depending on the product, the ECM approval service may require DINICAL calibration service. Check to see if DINICAL is in the product options.
ECMDOC	Printed EU declaration of conformity, EU certificate of verification, test certificate and metrological book (free download from our website, only for approved CE-M products). NET €.

High Resolution (d HR) (only at time of order)

Calibration Service (ACCREDIA/DAKKS) Only at Time of Order

CT4	ISO 17025 calibration certificate from 6 to 60 kg for single scale/platform. For precision and industrial scales, crane scales. The certificate is provided in digital format (pdf) and sent by e-mail.
CT5	ISO 17025 calibration certificate from 61 to 300 kg for single scale/platform. For precision and industrial scales, crane scales. The certificate is provided in digital format (pdf) and sent by e-mail.

Raising Frame

SGAQI-1	Stainless steel AISI 304 frame for 400x400mm platform. Loading surface h=600mm.
SGAXI-1	Stainless steel frame for 600x600mm platform. Loading surface h=600mm.

**Dini Argeo S.r.l. | Via della Fisica, 20 - 41042, Spezzano di Fiorano, Modena (MO), Italy |
Tel.: +39 0536 843418**

www.diniargeo.com