

# Fluke TP175 TwistGuard™ Test Probes



## Nøkkelfunksjoner

- Patented TwistGuard™ extendable tip shroud ensures electrical safety by reducing tip exposure while preserving versatility for different measurements
- Known for superior quality, ensuring reliable and accurate testing in industrial environments
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V
- see compatible products below

## Produktoversikt: Fluke TP175 TwistGuard™ Test Probes

- Adjustable tip length, allowing increased safety and precision
- Compatible with the TL22x series, TL238 and TL27 test leads
- Conforms to EN61010-031
- CAT II 1000 V, CAT III 1000 V, CAT IV 600, 10 A rating, CSA Listing
- One-year warranty

## Spesifikasjoner: Fluke TP175 TwistGuard™ Test Probes

Specifications	
Ratings	CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max., Pollution Degree 2
Exposed probe tip length	19 mm to 4 mm (0.75 inch to 0.16 inch)
Environmental ratings	-20°C to 55°C (-4°F to 131°F) altitude: 2000 m (6,562 ft)

TL175 and TL175E also available. TL175E includes removable 4 mm lantern tips that thread onto the lead tip.

Conforms to EN61010-031

## Modeller



### Fluke TP175

TwistGuard™ Test Probes

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Norge AS**  
Postboks 383  
1411 Kolbotn  
Tlf: 800 18 227  
E-mail: [cs.no@fluke.com](mailto:cs.no@fluke.com)  
[www.fluke.no](http://www.fluke.no)

©2026 Fluke Corporation. Med enerett.  
Informasjonen kan endres uten varsel. Vi tar  
forbehold om trykkfeil.  
03/2026

**Endring av dette dokumentet er ikke tillatt uten  
skriftlig tillatelse fra Fluke Corporation.**