



Bench scale with integrated rechargeable battery pack for maximum freedom and a practical printer connection

Features

- High mobility: thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department, etc.)
- Compact size, practical for small spaces
- Weighing with tolerance range (checkweighing): a visual and audible signal helps with portioning, dispensing or grading
- Summation of weight values
- RS-232 data interface for connection to a printer as standard

Technical data

- Backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, WxD 230x300 mm
- Overall dimensions WxDxH 340x320x110 mm
- Rechargeable battery pack integrated, as standard, operating time up to 50 h without backlight, charging time approx.
- Net weight approx. 3,2 kg
- Permissible ambient temperature 0 °C/40 °C

STANDARD



OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Reproducibility g	Linearity g	Smallest part weight (Normal) g/piece	Resolution Points	Options
							Calibr. Certificate DAkkS accr. KERN
FCD 3K-3	3	0,1	0,1	± 0,3	1	30.000	963-127
FCD 6K-3	6	0,2	0,2	± 0,6	2	30.000	963-128
FCD 10K-3	15	0,5	0,5	± 1,5	5	30.000	963-128
FCD 30K-2	30	1	1	± 3	10	30.000	963-128