

KERN OLM 170

KERN

The inverted metallurgical microscope for professional applications



Eye point	High Eye Point
Ocular magnifications	10x
Ocular visual field	20 mm
Ocular diameter	23,2 mm

Objective	
Objectives - Details	Objective Infinity Plan 10x / 0,25 LWD, anti-fungus
	Objective Infinity Plan 20x / 0,4 LWD, anti-fungus
	Objective Infinity Plan 5x / 0,15 LWD, anti-fungus
	Objective Infinity Plan 50x / 0,75 spring, LWD, anti-fungus
Objectives magnifications	5x / 10x / 20x / 50x

Illumination	
Illuminance	Reflected light
Illumination type incident light	LED
Illumination intensity incident light	5 W
Illumination dimmable	Incident light
Filter possible	✓

Focussing	
Field of view [Min]	0,4 mm
Field of view [Max]	4 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Condensor	
Condensor type	Standard

Power Supply	
Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	EURO UK
Power supply - Cable length	150 cm
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz

Category	
Brand	Optics
Product category	Microscope
Product group	Metallurgical microscope
Product family	OLM-1

Construction	
Dimension (WxDxH)	470x240x330 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	45°
Tube 360° rotation	✓
Tube type	Butterfly
Light distribution	20:80
Contrasting methods	Bright field Polarisation
Standard objectives	5x 10x 20x 50x
Lens quality	Infinity Plan
Nosepiece screw-in locations	4
Interpupillary distance [Min]	48 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-6
Diopter adjustment [Max]	6

Ocular	
Ocular type	Eyepiece HWF 10x / Ø 20mm with anti-fungus, high eye point
Ocular field width	HWF

KERN OLM 170



The inverted metallurgical microscope for professional applications

Power supply cable removable	removable
Input voltage device / power [Max]	5 V, 1 A
Power socket for mains adapter	Inside plus, outside minus

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	500×420×300 mm
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	9 kg
Shipping weight	12,6 kg

Product information

GTIN/EAN number	4045761356665
Trade number	90118000
REACH classification	no prohibited substances

Pictograms

STANDARD

