

KERN PDS 2000-2

Precision balance with flexible functionality and touch display



Maximum creep (30 minutes)	200 mg
Default unit	g

Display	
Display type	LCD
Display type	LCD
Display backlight	✓
Display screen size	140×48 mm
Display segments	7
Display digit height	20 mm
Languages of the user interface	English Symbol language

Construction	
Dimensions completely mounted (W×D×H)	213×322×101 mm
Dimensions weighing surface (W×D)	185×185 mm
Dimensions weighing surface	185×185 mm
Material housing	ABS plastic
Material weighing plate	stainless steel
Material display housing	glass
Level indicator	✓
Levelling feet adjustable	✓

Functions	
Sum memory function	✓
Recipe/summing level	Rez A (Net total)
Percentage determination	✓
Density determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	Hook (included in delivery)
Function for averaging under unstable weighing conditions	✓
Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	22.000
Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Reference quantity	5, 10, 20, 50, 100
Peak function	✓
Statistic function	✓

Category	
Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PDS

Measuring System	
Weighing system	Force compensation
Weighing capacity [Max]	2200 g
Readability [d]	0,01 g
Reproducibility	0,03 g
Linearity	± 0,03 g
Resolution	220.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	2 kg (F1)
Possible calibration points	1 kg; 2 kg
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,06 g
USP Minimum weight of sample (k = 2, U = 0.1%)	60 g
Construction type of the scale	Single-range balance
Units	kg g mg gn dwt tl (Tw) ozt ct lb N oz ffa
Maximum creep (15 minutes)	100 mg

KERN PDS 2000-2

KERN

Precision balance with flexible functionality and touch display

Auto-off interval(s) in mains power mode	off
Tare function	manual (multi)
Number of keys for operation	4

Interface

Interfaces	RS-232 standard USB-Device
------------	-------------------------------

Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	12 V; 2 A
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 10,8 mm

Environmental conditions

Ambient temperature [Min]	15 °C
Ambient temperature [Max]	25 °C
Humidity of environment [Min]	15 %
Humidity of environment [Max]	80 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	60 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for DAkkS calibration	963-127
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	370×470×340 mm
Shipping method	Parcel service
Net weight approx.	3,6 kg
Gross weight approx.	6 kg

Shipping weight 11,8 kg

Product information

GTIN/EAN number	4045761481916
Trade number	90160010
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

