

KERN FKS 30K-3

KERN

Networkable IP65 stainless steel bench scale with LED display and classification function



Date of creation: 01.07.2026

Category	
Brand	KERN
Product category	Industrial scale
Product group	Stainless steel scale
Product family	FKS
Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	30 kg
Readability [d]	0,002 kg
Reproducibility	0,002 kg
Linearity	± 0,006 kg
Resolution	15.000
Tare range	30 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	30 kg (M1)
Possible calibration points	10 kg; 20 kg; 30 kg
Stabilization time	2 s
Linearisation in dots	5
Eccentric loading at 1/3 [Max]	0,01 kg
Construction type of the scale	Single-range balance
Units	kg
	g
	gn
	ct
	lb
	oz
	ffa
	%
Maximum creep (15 minutes)	8 g
Maximum creep (30 minutes)	16 g
Default unit	kg

Display	
Display type	LCD
Display type	14 segment LCD
Display backlight	✓
Display screen size	120×40 mm
Display segments	14
Display digit height	23,5 mm
Languages of the user interface	English

Construction	
Dimensions completely mounted (W×D×H)	325×230×60 mm
Dimension display device (W×D×H)	228×70×50 mm
Dimensions weighing surface (W×D)	228×228 mm
Dimensions weighing surface	228×228 mm
Dimensions weighing platform (W×D×H)	228×228×60 mm
Material housing	plastic
Material weighing plate	stainless steel
Material platform	stainless steel
Material display housing	plastic
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓
Stand height	335 mm
Display device cable length	0,6 m
Platform Construction	Single-Cell
Load cells - number	1

Functions	
PreTare function	✓
Sum memory function	✓
Percentage determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Alibi memory	internal memory
Alibi memory - number of memory spaces	250.000
Function for averaging under unstable weighing conditions	✓
Capacity - Display	✓
Counting function	✓
Counting resolution (laboratory conditions)	15.000
Smallest piece weight when piece counting - laboratory conditions	2 g

KERN FKS 30K-3



Networkable IP65 stainless steel bench scale with LED display and classification function

Smallest piece weight when piece counting - normal conditions	20 g
Reference quantity	1, 5, 10, 20, 50, n (any number of pieces)
IP protection - complete device	IP65
IP protection - display	IP65
IP protection - platform	IP65
IP protection - load cell	IP65
Memory - total size	0,016 GB
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
Auto-off interval(s) in mains power mode	selectable
Tare function	automatic & manual (multi)
Number of keys for operation	6

Interface

Interfaces	RS-232 (optional, factory) Ethernet (optional, factory) WiFi (optional, factory) Alibi memory analogue (0 - 10 V) (optional, factory) analogue (4 - 20 mA) (optional, factory) Bluetooth BLE (v4.0) (optional, factory) USB-Device (optional, factory)
------------	---

Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	5V, 2,7A
Power socket for mains adapter	Magnetic plug
Battery / accumulator type	Li-Ion
Battery	no battery

Battery connection	Connector pin
Battery capacity	10.000 mAh
Battery voltage	3,7 V
Battery - Number of cells	1
Battery capacity (Wh)	37 Wh
Rechargeable battery	3,7V 10Ah
Rechargeable battery operating time - backlight on	15 h
Rechargeable battery operating time - backlight off	15 h
Rechargeable battery charging time	5 h
Rechargeable battery optional	Rchrg. battery optional - intern

Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Max]	80 %

Approval

CE mark	✓
---------	---

Services (optional)

Article number for adjustment at the location of installation	961-248
Article number for DAkkS calibration	963-128
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	450×350×160 mm
Shipping method	Parcel service
Net weight approx.	3,6 kg
Gross weight approx.	4,8 kg
Shipping weight	5 kg
Shipping volume weight	5 kg

Product information

GTIN/EAN number	4045761498303
Trade number	84238129
REACH classification	no prohibited substances

KERN FKS 30K-3

KERN

Networkable IP65 stainless steel bench scale with LED display and classification function

Pictograms

STANDARD



OPTION



FACTORY

