

KERN FPS 6K-3

KERN

Rugged stainless steel bench scale with IP68/IP69K protection for damp and outdoor areas



Date of creation: 30.06.2026

Category	
Brand	KERN
Product category	Industrial scale
Product group	Stainless steel scale
Product family	FPS

Measuring System	
Weighing system	Strain gauge
Number of weighing ranges	1
Weighing capacity [Max]	6 kg
Readability [d]	0,0005 kg
Reproducibility	0,0005 kg
Linearity	± 0,0015 kg
Resolution	12.000
Tare range	6 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	6 kg (M1)
Possible calibration points	3 kg; 6 kg
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,0025 kg
Construction type of the scale	Single-range balance
Units	kg
	g
	lb
	oz
	PCS
Units (if device is conformity assessed)	lb:oz
	kg
Maximum creep (15 minutes)	g
Maximum creep (30 minutes)	2 g
	4 g

Default unit	kg
Loadcell type	Tscale BX6

Display	
Display type	LCD
Display backlight	✓
Display screen size	100×35 mm
Display segments	6
Display digit height	25 mm
Languages of the user interface	English

Construction	
Dimension housing (W×D×H)	288×233×102 mm
Dimensions completely mounted (W×D×H)	288×233×102 mm
Dimensions weighing surface (W×D)	190×230 mm
Dimensions weighing surface	190×230 mm
Dimensions weighing platform (W×D×H)	230×190×20 mm
Material housing	stainless steel, plastic
Material weighing plate	stainless steel
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓

Functions	
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Counting function	✓
Counting resolution (laboratory conditions)	12.000
Smallest piece weight when piece counting - laboratory conditions	500 mg
Smallest piece weight when piece counting - normal conditions	5 g
Reference quantity	10, 20, 50, 100, 200
IP protection - complete device	IP68 IP69K
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
	off
	10 min
	30 min
Auto-off interval(s) in mains power mode	15 min
	3 min
	off
	10 min

KERN FPS 6K-3



Rugged stainless steel bench scale with IP68/IP69K protection for damp and outdoor areas

	30 min 15 min
Tare function	manual (multi)
Number of keys for operation	4

Power Supply

Supplied power supply	Accu & Power supply
Power supply type	USB including power supply
Plug-in power supply / adapter for countries - optional	EURO UK CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	5 V, 1 A
Power socket for mains adapter	Hollow plug inside plus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 9,4 mm
Battery / accumulator type	Li-Ion
Battery capacity	4.000 mAh
Battery voltage	3,7 V
Battery - Number of cells	2
Battery - Individual weight	154 g
Battery - Total weight	308 g
Battery - Construction	Inseparable connection of cells (pack)
Battery capacity (Wh)	14,8 Wh
Battery - Tests passed UN 38.3	✓
Rechargeable battery operating time - backlight on	50 h
Rechargeable battery operating time - backlight off	80 h
Rechargeable battery charging time	4 h
Battery/Accu connected	not connected, enclosed

Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Min]	5 %
Humidity of environment [Max]	85 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for adjustment at the location of installation	961-248
Article number for DAkkS calibration	963-128
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	340×295×165 mm
Shipping method	Parcel service
Net weight approx.	2,4 kg
Gross weight approx.	3,4 kg
Shipping weight	3,4 kg
Shipping volume weight	3,3 kg

Product information

GTIN/EAN number	4045761487987
Trade number	84238129
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

