Model:LY605T/LY805T LY610T/LY810T

Applications

- Inspection and maintenance of aviation aircraft, cars, ships, trucks, motorcycle engines
- Inspection and maintenance of instruments, machinery and electrical and electronic equipment
- systematic inspection of gas cylinder/tank inspection, pipeline inspection, air conditioning and vacuum system
- scientific experiment, address archeology and outdoor exploration, etc
- The place of family assistance inspection which is hard to see and touch

Applied to various fields:



vehicle-repair



Machinery



pipeline



Aircraft engine repair



cave Exploration



HVAC Repair

product parameter

Camera diameter	8.5mm	6mm	3.9mm
Coiled pipe length	1m、2m、3m、5m	1m、2m、3m、5m	1m、2m、3m、5m
Camera resolution	1920 *1080	1920 *1080	1920 *1080
Field of view	80°	70°	70°
Focal length	3cm-8cm	3cm-8cm	3cm-8cm
Frame rate	30fps	30fps	30fps
TF Card	32G	32G	32G
Image format	JPG	JPG	JPG
Video format	AVI	AVI	AVI
Waterproof grade	IP67	IP67	IP67
Battery	3000mAh polymer	3000mAh polymer	3000mAh polymer
Steering angle	Bi-directional 180°	Bi-directional 180°	Bi-directional 180°

product list

steerable endoscope
Host machine (5.0inch LCD) Type-C Cable
user manual
Len wipe cloth
product package Accessory

